

FARMALL 25SC

SUB COMPACT



Big performance in a little package

Our all NEW FARMALL 25SC is powered by a Naturally Aspirated 3-cylinder Tier 4 Diesel Engine and is coupled to a 2-range hydrostatic transmission with cruise control and two pedal direct control for forward and reverse. It is standard with 4WD, Differential lock, Hydrostatic Power steering and wet brakes to ensure you have all the driver comforts you would expect from a CASE IH Tractor.

Packed with features and additional implements options to make the CASE IH Farmall 25SC the best-in-class compact tractor for all round application.

HYDROSTATIC

INDUSTRIAL R4 LOADER 4 IN 1:

incl. GST

INDUSTRIAL R4 LOADER 4 IN1, MOWER DECK:

incl. GST

CASE IH

MODEL	FARMALL 25SC
ENGINE	
Emissions Level	Tier 4 B/Final
Gross Horsepower	24.7 hp (18.4 kW)
Rated Speed	3000 rpm
Number of Cylinders	3
Aspiration	Natural
Displacement	1.26L
Alternator	50 amps
Fuel Tank	25 L
PTO	
PTO Horsepower	17.2 hp (12.8 kW)
PTO Speed	540 rpm
PTO Type	Independent Electro-Hydraulic
Mid-PTO	Standard
Mid-PTO Speed	2500 rpm
TRANSMISSION	
Type	2 Range Hydrostatic / Dual Pedal
Maximum Forward Speed	13.3 kph
Cruise Control	Standard HST
Gear/Shuttle Type	Synchro
Rear Diff-lock Engagement	Mechanical
Brake Type	Wet Multi-Disc
HYDRAULICS & 3 POINT LINKAGE	
Implement Hydraulic Flow	17.1 L/min
Steering Hydraulic Flow	8 L/min
Total Flow	25.4 L/min
Remote Valves	1 Optional
3-Point Hitch	Chain Type Stabilizers /Fixed Link Ends
3-Point Lift Capacity @ ball ends	450 kg
3-Point Lift Capacity @ 24 in. (610 mm) behind ball ends	330 kg
3-Point Linkage	Category I
FRONT AXLE	
MFD	Standard
WEIGHTS AND DIMENSIONS	
Wheelbase	1425 mm
Length	2579 mm
Width	1187 mm
Height top of ROPS	2358 mm
Shipping Weight*	650 kg

* Tractor + Wheel equipment only

Features:

- Front end loader with Quick attach design
- Loader Lift capacity @ Bucket pivot pins 457 kg
- Loader Max lift height @ Pivot Pin 185 cm
- Loader Bucket width 122 cm
- Backhoe reach 292 cm from pivot pin
- Backhoe Bucket width 30.5 cm
- Backhoe swing arc 135 degrees
- Backhoe digging depth 191 cm
- Reversible operating seat
- Mid Mount Mower cutting width 152.4 cm
- Mid Mount mower side discharge



Scan the QR code for Brochure



Locals Supporting Locals

