

DEUTZ-FAHR

6125C RV

40 KM/H

136HP



TOTAL CONFIGURABILITY

With 136 HP and a range of customisable options, these tractors offer limitless potential for configuration. Equipped with powerful hydraulic systems featuring load-sensing pumps with capacities of up to 120 l/min, they can be precisely tailored to meet even the most specialised requirements.

All 6C Series models come with four cylinder FarmMotion Diesel Engine, TopVision 4-pillar cabs and a choice of all-new SDF Smart Farming Solutions.

With a reputation for durability and quality, the Deutz-Fahr 6125C RV is an ideal choice for farmers looking for a high-performance, efficient tractor capable of handling a variety of tasks with ease.

ENGINE

- FARMotion LRC Diesel Engine
- 4 Cyl/3849cc Turbocharged/Intercooled
- Electronically Controlled
- No AdBlue / No DPF
- Liquid/Oil Cooled with Viscous Fan
- High Pressure Diesel Injection Common Rail
- 136 Max Hp @ 2200 rpm (ECE R120)
- 10Hp Power Boost
- Torque 524 Nm @1600 rpm
- Engine Speed Programming
- Powercore Air Filter with Dust Ejectors
- VISCO cooling fan
- Side Vertical Exhaust
- Fuel Tank 200 Litres

TRANSMISSION

- 20+16 RV Shift Transmission
- Automatic Power shift
- Wet clutch Powershuttle
- Shuttle Modulation – 5 Stage (Sense Clutch)
- 2 Ranges Heavy & Normal
- Stop and Go Function
- Front Wheel Assist – Push Button
- 4 Wheel Independent Braking
- Hydraulic Parking Brake (HPB)
- 100% Front & Rear Diff Lock - Push Button
- ASM Engagement for 4WD & Difflock
- 40 km/h Road Speed

PTO

- Independent Wet Multidisc Clutch
- 3 Speed PTO 540/540E/1000
- Push Button Control in Cab/Fender
- Auto PTO
- Interchangeable PTO Spline Function
- 1" 3/8 – 6 Spline PTO Shaft

WHEEL EQUIPMENT & MISCELLANEOUS

- 440/65R28 Front - 540/65R38 Rear
- With Rear Guard Extensions
- Front Weight Frame 70kg with hitch
- ISO 11786 7 pin Socket + 12V Socket
- Front Dynamic Fenders

OPERATOR ENVIRONMENT

- TopVision Pro Air Conditioned Cab
- Mechanical Cabin Suspension (SS011)
- Rvshift Satellite Armrest with ADVANCED Joystick (AO002)
- Full Control with Programable 3 Jolly Buttons
- Max-Professional Air Seat
- Tilt and Telescopic Steering Wheel
- SDD Rapid Steering Circuit
- INFOCENTER 5" Digital Display
- Trainee Seat with Seatbelt
- MP3 Radio Player with Quad Speakers
- Telescopic Mirrors
- 8 Cabin Work lights
- 2 Work lights on Cab post
- 4 Bonnet Front Work lights
- Rotating Beacon

HYD/LINKAGE/DRAWBAR

- Closed Centre Hydraulic System
- 120 L/min Hyd Pump
- Hi Flow & Free Flow Return
- 3 rear high flow distributors with one electric diverter with flow regulator and quick couplers (3 Float) (8 rear outlets) Remotes with Float (GP299) Flow Control on All Remotes
- AGROTRONIC EHR with Position & Draft
- External Raise & Lower on Rear Fenders
- Cat II Hook Ends
- 7000 kg Lift Capacity
- Swinging Drawbar – CAT A

WEIGHTS & DIMENSIONS

Wheelbase: **2510mm**

Length: **4530mm**

Total Height: **2785mm**

Total Weight: **4900kg**

DEALER DETAILS