

6135C RV



TOTAL CONFIGURABILITY.

With 143 HP and a range of customisable options, these tractors offer limitless potential for configuration. Equipped with powerful hydraulic systems featuring load-sensing pumps with capacities of up to 120 l/min, they can be precisely tailored to meet even the most specialised requirements.

All 6C Series models come with four cylinder FarmMotion Diesel Enginess, TopVision 4-pillar cabs and a choice of all-new SDF Smart Farming Solutions.

With a reputation for durability and quality, the Deutz-Fahr 6135C RV is an ideal choice for farmers looking for a high-performance, efficient tractor capable of handling a variety of tasks with ease.

ENGINE

- → FARMotion LRC Diesel Engine
- → 4 Cyl/3849cc Turbocharged/Intercooled
- → Electronically Controlled
- → No AdBlue / No DPF
- → Liquid/Oil Cooled with Viscous Fan
- → High Pressure Diesel Injection Common Rail
- → 143 Max Hp @ 2200 rpm (ECE R120)
- → 6Hp Power Boost
- → Torque 550 Nm @1600 rpm
- → Engine Speed Programming × 2
- → Powercore Air Filter with Dust Ejectors
- → VISCO cooling fan
- → Side Vertical Exhaust
- → Fuel Tank 200 Litres

TRANSMISSION

- → 20+16 RV Shift Transmission
- → Automatic Power shift
- → Wet clutch Powershuttle
- → Shuttle Modulation 5 Stage (Sense Clutch)
- → 2 Ranges Heavy & Normal
- → Stop and Go Function
- → Front Wheel Assist Push Button
- → 4 Wheel Independent Braking
- → Hydraulic Parking Brake (HPB)
- → 100% Front & Rear Diff Lock Push Button
- → Front Axle Suspension
- → 50 km/h Road Speed
- → Pre-Arrangement For Front End Loader

PTO

- → Independent Wet Multidisc Clutch
- → 3 Speed PTO 540/540E/1000
- → Push Button Control in Cab/Fender
- → Auto PTO
- → Interchangeable PTO Spline Function
- \rightarrow 1" 3/8 6 Spline PTO Shaft

WHEEL EQUIPMENT & MISCELLANEOUS

- → Fixed Fully Welded Radial Wheel Equipment
- → 540/65R24 Front -600/65R38 Rear
- → 260mm With Rear Guard Extensions
- → Pre Arrangement for Front Linkage + PTO
- → Front Weight Frame 70kg with hitch
- → ISO 11786 7 pin Socket + 12V Socket
- → Front Dynamic Fenders

OPERATOR ENVIRONMENT

- → TopVision Pro Air Conditioned Cab
- → High visibility transparent roof
- → FOPS-compliant (polycarbonate hatch) with sunshade grid
- → Mechanical Cabin Suspension
- → Rvshift Satellite Armrest with **ADVANCED Joystick**
- → Full Control with Programable 3 Jolly Buttons
- → Max-Professional Air Seat
- → Tilt and Telescopic Steering Wheel
- → SDD Rapid Steering Circuit
- → INFOCENTER 5" Digital Display
- → COMFORTIP Sequential Drive System
- → Trainee Seat with Seatbelt
- → DAB MP3 Radio Player with Quad Speakers
- → Telescopic Mirrors
- → WOLP (Work Operating Light Panel)
- → 8 Cabin Work lights
- → 2 Work lights on Cab post
- → 4 Bonnet Front Work lights
- → Rotating Beacon

HYD/LINKAGE/DRAWBAR

- → Closed Centre Hydraulic System
- → 120 L/min Hyd Pump
- → Power Beyond Valve and Load Sensing Lines
- → Hi Flow & Free Flow Return
- → 3 Sets of Mechanical -Hyd Remotes with Float
- → Flow Control on All Remotes
- → AGROTRONIC EHR with Position & Draft
- → External Raise & Lower on Rear Fenders
- → Cat II Hook Ends
- → 5000 kg Lift Capacity
- → Swinging Drawbar CAT A

WEIGHTS & DIMENSIONS

Wheelbase: 2510mm Length: 4530mm Total Height: 2785mm Total Weight: 4900kg

DEALER DETAILS

