

# DEUTZ-FAHR

# 4100E GS

102HP

40 KM/H POWERSHUTTLE

WET CLUTCH

SPEC B



## WELCOME TO THE NEW 4E GS SERIES

The new 4E GS ROPS is the ideal tractor for smaller farms and operators, local authorities and horticultural businesses.

With a choice of three different models with power outputs from 76 HP to 102 HP all paired with a Wet Clutch Powershuttle, this range is the perfect utility tractor for a range of different applications.

## ENGINE

- FARMotion LCR Diesel Engine
- 3 Cyl/2887cc Turbocharged Intercooled
- Liquid/Oil Cooled
- Engine speed programming
- High Pressure Diesel Injection/Common Rail
- 102Hp @ 2200 rpm (ECE R120)
- 5Hp Power Boost
- Torque 417 Nm @1400 rpm
- Downswept exhaust
- 75lt Fuel Capacity

## TRANSMISSION

- **30/30 Forward/Reverse Gears**
- Wet Clutch Power Shuttle
- Shuttle Modulation with 5 Settings
- 5 Speeds/3 Ranges/**2 Power Shifts**
- 0.246 – 40Kp/h ECO 1800 RPM
- Comfort Clutch with Stop and Go Function
- **Wheel Independent Braking with LOGIC valve**
- Push Button 4WD and Diff lock 100% Locking

## PTO

- Independent Rear PTO
- 540/ 750 Speed PTO
- 540 PTO @ 1967 Rpm
- 540E PTO @ 1560 Rpm
- 1"3/8 - 6 Spline PTO Shaft

## WHEEL EQUIPMENT & MISCELLANEOUS

- Adjustable Radial Wheel Equipment
- **11.2 – 24 front 16.9 – 30 rear tyres**
- **Front Weight Frame 8x40kg weights (320kg)**
- Rear Weight Ballast 180 kg
- Front Dynamic Fenders suit std wheels

## OPERATOR ENVIRONMENT

- 2 Post ROPS Frame
- Flat Floor ISO Mounted Platform
- Rubber Floor Mat
- Ergonomic Controls
- Telescopic and Tilting Steering Wheel
- Digital Dash
- Deluxe PVC Mechanical Seat
- Sun Canopy
- Telescopic Mirrors
- 2 Rear Work lights
- Rotating Beacon

## HYD/LINKAGE/DRAWBAR

- Open Centre Hydraulic System
- 56 l/min Hyd Pump
- Separate 20 L/min Steering Pump
- 3 Sets of Remotes
- Kickout/Detent/Float
- Mechanical Three Point Linkage
- **EASYLIFT raise and lower switch**
- Position & draft control settings
- Cat 2 hook ends
- 3500kg lift capacity
- Swinging Drawbar - CAT A

## WEIGHTS & DIMENSIONS

Wheelbase: **2106mm**

Length: **3860mm**

Total Height: **3250mm**

Total Weight: **2498kg**

## DEALER DETAILS