

## CK3010 SERIES



# **IDEAL TRACTOR FOR**

The CK3010 is equipped with a performance proven, heavy duty HST drive unit to handle the increased horsepower of this stylish and popular compact Kioti

Single pedal controls make changing between forward and reverse easy, without clutching or hand shifting, and the operator's hands remain free for steering and implement control.

The CK3010 features a 3-cylinder, 30 hp water-cooled diesel engine. Its travel speed is adjustable using both a hand lever and a foot accelerator pedal. With a fuel

tank capacity of 25L, it ensures efficient and sustained operation.

A heavy duty front axle and standard 4WD guarantee powerful traction. The CK3010 has two infinite travelling speeds: 17 km/h in forward; and 12 km/h in reverse.

It comes with a hydrostatic transmission, standard rear differential lock, wet disc brakes and a standard 540/rpm PTO. The CK3010 embodies the ideal machine for any lifestyle.



**CK3010 ROPS** 







### CK3010 COMPACT ROPS

#### **ENGINE**

- Daedong 3A139LWB
- Liquid Cooled 3 Cylinder Diesel
- 1,393cc Displacement
- 30 HP @ 2600 rpm
- 25 Litre Fuel Tank Capacity

#### **TRANSMISSION**

- Dry Single Plate Clutch
- 2 Range Hydrostatic
- Standard Differential Lock
- 4 Wheel Drive

#### **HYDRAULICS & LINKAGE**

- Tandem Gear Pump
- 42.9 lpm Max. Flow Pump Capacity
- Category 1 Three Point Hitch
- 546kg Max Lifting Capacity @ 610mm Behind Lift
- Hydraulic Lift Position Control
- Power Steering

#### **POWER TAKE OFF**

Independent 540 rpm Rear

#### **BRAKES**

Wet Disc Type

#### **OPERATOR ENVIRONMENT**

- Ergonomic Operator Station
- Illuminated Instrument Panel
- 12 volt Power Outlet
- High Back Seat
- Step Through Platform
- Front Work Lights
- Easy Access Engine Bay

#### **TRAVEL SPEEDS**

- Forward 0 17.1 kph
- Reverse 0 12 kph

#### **DIMENSIONS**

Overall Length (inc 3PL) 2790mm

Overall Height 2108mm

Overall Width (min tread)
1250mm

Wheelbase 1520mm

Min. Ground Clearance 330mm

Weight 1025kg

TYRES Industrial Front 23 x 8.5 — 12

Industrial Rear 12 - 16.6



\*Note: The specifications are subject to change for the purpose of improvement without any notice. Images for illustration purposes only.

