



PX9520 SERIES

ROPS



VERSATILE WORKHORSE.

The dynamic and acclaimed PX range with a weight of 4 tonne is designed for serious farming and the ideal tractor for front end loader work. With a generous 120 litre fuel tank and a fuel efficient engine, the PX9520 can keep on working for a long time between fuel breaks. Equipped with hydrostatic power steering, this tractor provides smooth responsive steering that requires minimal operator effort.

Featuring a versatile transmission system that provides smooth operation and precise control, the PX9520 makes it easy to navigate challenging terrains and heavy workloads. Additionally, it is built with durable components and straightforward maintenance points, ensuring longevity and ease of upkeep.

With its combination of power, safety, and user-friendly features, the Kioti PX9520 ROPS tractor is an excellent choice for farmers seeking dependable performance and versatility in their agricultural operations.



PX9520 ROPS
95HP



@kiotiaustralia



@kiotitractorsaustralia



kioti.com.au



PX9520 UTILITY ROPS

ENGINE

- Perkins 1104C-44TTG
- Liquid Cooled 4 Cylinder Diesel Turbo
- 4399cc Displacement
- 95 HP @ 2200 rpm
- 120 Litre Fuel Tank Capacity
- Dual Stage Air Cleaner

TRANSMISSION

- Synchro Forward and Reverse Shuttle
- 16F X 16R
- Differential Lock
- 4 Wheel Drive

HYDRAULICS & LINKAGE

- Implement Pump - 48.4 lpm
- Power Steering Pump - 30.8 lpm
- Total Hydraulic Flow - 79.2 lpm
- Category 2 Three Point Linkage
- Hook Type 3PL
- 2400kg Maximum Rear Lift Capacity
- Power Steering
- Clevis Type Rear Draw Bar

POWER TAKE OFF

- Independent
- 540 / 1000 rpm
- Auto PTO

BRAKES

- Wet Multi Disc Type

OPERATOR ENVIRONMENT

- High Quality Fully Adjustable Seat with Armrests and Backrest
- Adjustable Steering Wheel and Instruments
- Flat Operator Deck

TRAVEL SPEEDS

- Forward 0.82 - 38.36 kph
- Reverse 0.80 - 37.33 kph

DIMENSIONS

Overall Length (inc 3PL)
4120mm

Overall Height
2950mm

Overall Width (min Tread)
2000mm

Wheelbase
2305mm

Ground Clearance (Min)
475mm

Weight
3500kg

TYRES
AG Tyres Front
12.4 - 24 8PR

AG Tyres Rear
18.4 - 34 8PR



OPTIONAL EQUIPMENT



BALE SPIKE



PALLET FORK

*Note: The specifications are subject to change for the purpose of improvement without any notice. Images for illustration purposes only.

DEALER DETAILS



SCAN TO
LEARN MORE